



Apple Cabin House Configuration List 5800 × 2480 × 2500 mm

Configuration Parameters

Category	Material Name	Material Specification
Frame	Square tube	120×80×2.5m
		60*40*1.5m
		40×80×1.5m
		50×50×1.0m
		40×40×1.2m
Wall	Plastic flooring	2.0mmPlastic Flooring
	Cement fiberboard	18mm
	Galvanized sheet	1.2mm
	EPS insulation	75mm
	OSB board	2×3mm
Top	Interior wall bamboo-wood	0.7cm
	EPS insulation	Thickness75mm
	Galvanized sheet	1.2mm
	OSB board	1.22*2.44m
Bottom	Ceiling	Bamboo-Wood Fiberboard
	Plastic flooring (wood flooring can be customized)	2.0mmPlastic
	Cement fiberboard	18mm, asbestos-free
Door & Window	Door	Thermal break aluminum, 0.98*2.4m
	Window	Thermal break aluminum, 1.2*1.5m
	Glass Curtain Wall	ntegrated curtain wall
	Door and Window Frame	Aluminum cladding package
Paint	Special Paint for Galvanized and Stainless	Alloy Paint Finish
Electrical Components	Main Circuit	Lighting Circuit (Single Branch)
	Switches & Outlets	Socket Circuit (Single Branch)
	Lighting Circuit	Air Conditioning Socket Circuit (Single Branch)
	Residual Current Device (RCD) / Ground Fault Circuit Interrupter (GFCI)	Main Circuit Breaker
10A Five-hole Socket/ 16A Air Conditioning Socket /10A Switch	National Standard	